

WILSON See-Thru Strip Curtains

Easily pass into and out of noisy, hazardous or energy-wasting work areas. No struggling with heavy, awkward doors. Wilson See-Thru Strip Curtains automatically reseal with non-gap closure after pass through.

Safety


- Safe observation of dangerous areas.
- Containment of hazardous materials.
- Minimize traffic hazards

Comfort

- Reduce noise
- Allow visibility
- Maintain temperature

Convenience

- Tough and long lasting
- Sustains high impact or abrasion
- Resistant to most inorganic acids, alkalines, salts & static
- Unlimited Applications
- Energy efficient



SOUND TRANSMISSION—LOSS dB

Frequency, Hz	80 mil Sheet	160 mil Sheet
100	7	13
125	8	14
160	6	12
200	4	10
250	13	19
315	13	19
400	16	22
500	17	23
630	19	25
800	20	26
1000	22	28
1250	23	29
3100	30	36
4000	31	37
5000	33	39


How To Order:

1. Determine size required (height and width)
2. Based on application and height, determine strip thickness. Environmental conditions will affect this decision. Tinting is required for welding.
3. Determine whether overlap is partial or full.
4. Specify part number when placing order.
5. Support hardware is ordered as a separate item.

Full overlap is recommended for maximum sound reduction.

Wilson See-Thru Strip Curtains are adaptable to most any shape in most widths and heights.

Reinforced material used for extra height applications.



Call 1.800.423.4277 or visit us at www.wilsonindustries.com