

## Tri-Fold Screen

Wilson Tri-Fold Screen offers flexible, lightweight and durable protection for a variety of welding and industrial applications. Our unique swing arm feature adapts to any angle or shape. Wilson Tri-Fold consists of sturdy 1" square steel tubing, compression brackets, platform legs and wraparound safety curtain. This screen measures 6' high with a 6' wide center panel and 4' wide side panels.

Tri-Fold is available in all Wilson See-Thru fabrics and may be combined with a Rip-Stop border to color coordinate your work areas.

### TRI-FOLD SCREENS

Part Number	Transparent Welding Curtain	Rip-Stop Border
T36464-2585	Spectra Orange See-Thru	Yellow Rip Stop
T36464-2565	Spectra Orange See-Thru	Blue Rip-Stop
T36464-5065	Gold (yellow) See-Thru	Blue Rip-Stop
T36464-5035	Gold (yellow) See-Thru	Red Rip-Stop
T36464-25	Spectra Orange See-Thru	None
T36464-50	Gold (yellow) See-Thru	None

Per OSHA recommendations, all curtains allow 1ft. clearance at floor.



#### Custom Transparent Curtain Color Selection



Spectra Gold Green Gray Plasma

#### Custom Border Color Selection



Blue (65) Green (95) Yellow (85) Red (35) Black (55)



\*\*Rip-Stop is available in Green (#95), Yellow (#85), Blue (#65), Black (#55) or Red (#35). Insert fabric number to complete part number.

## Modular Screen

The Wilson Modular Screen is our industrial grade frame. Designed to be used individually or quickly hinged together to form multiple panel units. Modular Screens are durable, lightweight and easily assembled. Use these screens for welding, grinding, cutting, and brazing protection.

- Steel Tubing, 7/8" O.D.
- 24" crossbar legs standard with all screens
- Exclusive corner clamp and hinge assembly
- Wilson safety curtain

### MODULAR SCREENS

H x W Each Panel	Spectra Orange See-Thru	Gold (Yellow) See-Thru	Green See-Thru	Gray See-Thru	Plasma See-Thru Dins#32506	Rip Stop	Canvas Duck	Frame Only	H x W Curtain Cut Size*
6'x4'	M 64-25	M 64-50	M 64-60	M 64-80	M 64-90	M 64**	M 64-15	M 64	5'x4'
6'x6'	M 66-25	M 66-50	M 66-60	M 66-80	M 66-90	M 66**	M 66-15	M 66	5'x6'
6'x8'	M 68-25	M 68-50	M 68-60	M 68-80	M 68-90	M 68**	M 68-15	M 68	5'x8'

Per OSHA recommendations, all curtains allow 1ft. clearance at floor.



### Wilson Stur-D-Screen Frame:

The remarkable strength of the Wilson **Stur-D-Screen** frame is demonstrated here. Solid square steel tubing, exclusive bolted corner clamps and platform legs provide exceptional strength and sturdiness - enough to support these 200 pound welding tanks.

Call 1.800.423.4277 or visit us at [www.wilsonindustries.com](http://www.wilsonindustries.com)